

# METEOR PARQUET



## ANTI-SLIP SELF-POLISHING EMULSION FOR TREATED AND UNTREATED PARQUET

- Anti-slip effect tested by UL laboratories
- Very high level shine
- Excellent resistance to traffic



Formulated with a mixture of polymers and waxes specifically created for the porosity of wood floors. Guarantees effective protection and restores the original level of shine. Registered with Underwriters Laboratories Inc. as anti-slip, high resistance wax.

### HOW TO USE

After carefully removing wax using a wax stripper from the SUTTER PROFESSIONAL range, apply one or two coats of wax using the special wax applicator. Leave to dry approximately 30 - 60 min. between one coat and the next. Also suitable for UHS spray cleaning or spray buffing maintenance.

### DILUTION

Ready to use

### TECHNICAL DATA

**ASPECT:** Opaque liquid

**COLOR:** Yellow

**PERFUME:** Honey

PH	Active substance [%]	Density (g/ml)	Pressure (bar)	Viscosity (cP)	Total dry residue [%]
8,5 ± 0,5		1.025			12-13

### WARNINGS

If medical advice is needed, have product container or label at hand. Keep out of reach of children. Contents METHYLCHLOROISOTHIAZOLINONE, METHYLISOTHIAZOLINONE: May produce an allergic reaction.

## METEOR PARQUET

### NOTES

Protective wax for floors. Do not apply METEOR PARQUET at temperatures below 10° C. Keep away from freezing. PRODUCT FOR PROFESSIONAL USE ONLY. SAFETY DATA SHEET AVAILABLE FOR PROFESSIONAL USERS.

### PACKAGING

Code	Size	Quantity	Pallet
4155	kg 5	4	9x4=36