

COTTO WP



WATER-BASED AND OIL-REPELLENT IMPREGNATING AGENT

- High waterproofing power without altering the appearance of floor
- Also suitable for indoor use
- Ideal for terracotta and natural stones

Specific formulation for the water-oil repellent treatment of terracotta, natural stone and bare concrete. Provides excellent waterproofing without altering the appearance by avoiding the increase of efflorescence.

HOW TO USE

After carefully removing wax using a wax stripper from the SUTTER PROFESSIONAL range, and after descaling using a special acid (for terracotta floors), apply one or two coats of COTTO WP using the special wax applicator. Leave to dry approximately 30-60 min. between one coat and the next. To get a glossy finish, afterwards apply the product METEOR EXTRA SOLV or a metal wax.



DILUTION

Ready to use.

TECHNICAL DATA

ASPECT: Clear liquid
COLOR: Colorless/yellow
PERFUME: Lightly technical
COV: 0,00%

PH	Active substance [%]	Density (g/ml)	Pressure (bar)	Viscosity (cP)	Total dry residue [%]
5,1 ± 0,5		1			1,3 ± 0,1

NOTES

Keep away from freezing. Natural protective effect, not film. In case of outdoor finishes, do not apply the product if rain or high humidity are expected. Some floors may be difficult to penetrate and/or anchor the treatment. Check adherence in a small area of the floor before applying the product.

Before use, please always refer to the Technical Data Sheet and the Safety Data Sheet, with the exposure scenario, of the product. Use the PPE specified in the Safety Data Sheet.

Sutter Professional cannot be considered liable for any damages due to improper product use.

Only for professional use. Safety data sheet available on request.

PACKAGING

Code	Size	Quantity	Pallet
4302	Kg 5	4	9x4=36